



Cost-Effective High Resolution, Security Surveillance TFT Color LCD Monitors

Models:
ULM-153 15"
ULM-173 17"
ULM-193 19"



Features

- Three Screen Sizes (15", 17" and 19") available
- High Resolution Image 550TVL
- Composite 1& 2-NTSC/PAL(BNC), S-Video(Y/C) and Analog VGA(D-Sub)
- 16.2 Million Colors
- Wider Viewing Angle
- Loop-through Composite Video
- Fast Response Time (8msec/15", 5msec/17" & 19")
- Two Audio Speakers
- Power AC 100V ~ 240V
- All Safety Standards (FCC, UL, RoHS)

Specifications

| | | ULM-153 | ULM-173 | ULM-193 |
|----------------------------|-----------------------------|--|----------------------|----------------------|
| Panel: | Type: | Amorphous Active Matrix Super TFT LCD | | |
| | Viewable size: | 15" (TN) diagonal | 17" (TN) diagonal | 19" (TN) diagonal |
| | Pixel pitch: | 0.297mm x 0.297mm | 0.264mm x 0.264mm | 0.294mm x 0.294mm |
| | Number of pixels: | 1024 x 768 | 1280 x 1024 | 1280 x 1024 |
| | Display colors: | 16 Million Colors | | |
| | Brightness: | 250cd/m2 | 300cd/m2 | 300cd/m2 |
| | Contrast ratio: | 600:1 | 1000:1 | 800:1 |
| | Response time: | 8msec. | 5msec. | 5msec. |
| | Viewing angle(L/R): | 80/80 | 80/80 | 80/80 |
| | Viewing angle(U/D): | 80/80 | 80/80 | 75/80 |
| Frequency: | Horizontal: | 31 ~ 48KHz | 31 ~ 64KHz | |
| | Vertical: | 56 ~ 75Hz | | |
| 2Line comb filter: | | Built-in | | |
| Resolution: | Horizontal: | 550TVL | | |
| Speakers: | | Built-in (2pcs) | | |
| Multimedia: | Sound: | RCA x 1 & Mini-Jackx1, 300mVrms, High Impedance | | |
| Display area: | Max. (W X H): | 12.0" x 9.0" | 13.3" x 10.6" | 14.8" x 11.9" |
| Menu controls: | | Brightness, Contrast, Color, Sharpness, Tint, B-Screen, Color Tone, Volume | | |
| Power: | Embedded DC adaptor: | AC 100 ~ 264V, 50/60Hz | | |
| Input signal: | Input: | RGB(15pin), composite (BNC) 1 & 2, S-Video (Mini-DIN), Audio (RCA) | | |
| | Output: | Composite (BNC) 1 & 2 | | |
| Compatibility: | Analog RGB: | Up to XGA | VGA, SVGA, XGA, SXGA | |
| | Video: | NTSC/PAL Standard | | |
| Regulations: | EMI: | FCC Class A | | |
| | Safety: | CE, UL, cUL | | |
| Wall mount: | | VESA Standard 100mm x 100mm | | |
| Dimensions (WxHxD): | Product: | 13.8" x 13.7" x 7.9" | 15" x 15.4" x 7.9" | 19.5" x 19.9" x 9.3" |
| | Ship in: | TBD | TBD | TBD |
| Weight: | Product: | 8.14 lbs | 13.64 lbs | 18.54 lbs |
| | Ship in: | TBD | TBD | TBD |
| Power consumption: | Maximum: | 36W | 50W | 50W |
| | DPMS: | Under 3W | | |
| Accessories: | Standard: | Desktop stand, PC Cable, Remote Control, Battery AAAx2, AC Adaptor, Cord | | |
| | Option: | Tilt & Swivel Wall Mount (IK-LCD-75-100-B) | | |

Design and specifications are subject to change without notice.

Catalog No. 120808-1

Ikegami

IKEGAMI ELECTRONICS (U.S.A.), INC.

URL <http://www.ikegami.com>

**HEADQUARTERS
WESTCOAST OFFICE**

37 Brook Avenue, Maywood, NJ 07607 Phone (201)368-9171 Fax (201)569-1626
2631 Manhattan Beach Blvd., Redondo Beach, CA 90278
Phone (310)297-1900 Fax (310)536-9550

**SOUTHWEST OFFICE
MIDWEST OFFICE
SOUTHEAST OFFICE**

773 Bearden Road, Waxahachie, TX 75167 Phone (972)869-2363 Fax (972)556-1057
747 Church Road, Unit C1, Elmhurst, IL 60126 Phone (630)834-9774 Fax (630)834-8689
5200 N.W. 33rd Avenue, Suite 111, Fort Lauderdale, FL 33309
Phone (954)735-2203 Fax (954)735-2227